

共通仕様	
直径公差	+0/-0.13mm
厚さ公差	±0.25mm
開口径	直径の80%以上
平面度	$\lambda/4$ (Φ1インチ @ 632.8nm)
平行度	3 arc min
S/D	40/20

型番	材質	直径 (インチ/mm)	厚さ (インチ/mm)
IN-WBG-0.5x2-2	Ge	0.5x2.0	2
IN-WBG-0.6x2.5-2	Ge	0.6x2.5	2
IN-WBG-0.7x2.9-2	Ge	0.7x2.9	2
IN-WBG-1.0x4.1-3	Ge	1.0x4.1	3
IN-WBG-1.5x3.9-4	Ge	1.5x3.9	4
IN-WBG-2.0x5.2-5	Ge	2.0x5.2	5
IN-WZB-26.4x10.2-2	ZnSe	26.4x10.2(mm)	2
IN-WZB-0.7x1.8-2	ZnSe	0.7x1.8	2
IN-WZB-0.6x1.5-2	ZnSe	0.6x1.5	2
IN-WZB-0.5x1.3-2C(Corner cut)	ZnSe	0.5x1.3	2
IN-WZB-0.5x1.3-2	ZnSe	0.5x1.3	2
IN-WZB-25x66-3	ZnSe	25x66(mm)	3
IN-WZB-25x50-3	ZnSe	25x50(mm)	3
IN-WZB-20.3x52.8-3	ZnSe	20.3x52.8(mm)	3
IN-WZB-1.0x2.6-3	ZnSe	1.0x2.6	3
IN-WZB-53x20-3	ZnSe	53x20(mm)	3
IN-WZB-1.5x3.9-4	ZnSe	1.5x3.9	4
IN-WZB-2.0x5.2-5	ZnSe	2.0x5.2	5
IN-WZB-30x75-5	ZnSe	30x75(mm)	5