

共通仕様	
直径公差	+0/-0.13mm
厚さ公差	±0.25mm
焦点距離公差	±2%以下
光軸ズレ	3 arc min 以下
開口径	直径の90%以上
面精度	$\lambda/2$ (Φ1インチ @632.8nm)
面品質	40/20
反射公差	±3% @ 1064nm

型番	直径 (mm)	厚さ (mm)	反射率 (%)
IN-RFS-0.5-6.35-65%R	12.7	6.4	65%
IN-RFS-0.5-6.35-80%R	12.7	6.4	80%
IN-RFS-0.5-6.35-85%R	12.7	6.4	85%
IN-RFS-0.5-6.35-90%R	12.7	6.4	90%
IN-RFS-0.5-6.35-95%R	12.7	6.4	95%
IN-RFS-0.75-9.5-85%R	19.1	9.5	85%
IN-RFS-0.75-9.5-80%R	19.1	9.5	80%
IN-RFS-0.75-9.5-70%R	19.1	9.5	70%
IN-RFS-0.75-9.5-30%R	19.1	9.5	30%
IN-RFS-20-5-80%R	20	5	80%
IN-RFS-20-5-85%R	20	5	85%
IN-RFS-1.0-9.5-17%R	25.4	9.5	17%
IN-RFS-1.0-9.5-20%R	25.4	9.5	20%
IN-RFS-1.0-9.5-25%R	25.4	9.5	25%
IN-RFS-1.0-9.5-50%R	25.4	9.5	80%
IN-RFS-1.0-9.5-85%R	25.4	9.5	85%